

FASTPAYHOTELS PROVIDER XML 1.1 INTEGRATION API

| | |
|------------------|-------------------|
| Current Version: | 2.1 – NOV -2023 |
| API Type: | XML 1.1 - NO SOAP |

Version

| Date | Changes |
|-----------------|--|
| 05-July-2020 | - Document use of Echo Token and Timestamp in all call requests |
| 22-May-2021 | - DateTime format review. ISO Format - BookingRetrievalRQ optional request parameters review. |
| 11- Jan - 2022 | - Add fields ClosedToArrival and ClosedToDeparture into HotelAvailRateUpdate message. - Changed due to typo error BookingRetrieval > Card Details > Expiration Date Format - Price Model Room + Extras |
| 08 – Nov - 2022 | - Clarification and amendments in input request XML Price Models examples vs XML Parameters Description - Child Rate Calculation Definition - Booking Retrieval XML examples |
| Nov-2023 | - Added AmountBeforeTax node to ARI Push and Booking Retrieval |

Contents

| | |
|--|----|
| 1. Introduction..... | 4 |
| 2. Endpoint..... | 4 |
| 2.1. Standard endpoint | 4 |
| 2.2. Custom endpoint | 4 |
| 3. Methods..... | 5 |
| 3.1. GetHotelInfo..... | 5 |
| 3.1.1. Objective | 5 |
| 3.1.2. Prerequisites | 5 |
| 3.1.3. Sequence of events | 5 |
| 3.1.4. Input request XML..... | 5 |
| 3.1.5. Request XML Parameters Description | 6 |
| 3.1.6. Successful response XML | 6 |
| 3.1.7. Error response XML..... | 7 |
| 3.1.8. Output XML parameters description | 7 |
| 3.2. HotelAvailRateUpdate..... | 8 |
| 3.2.1. Objective | 8 |
| 3.2.2. Request XML..... | 8 |
| 3.2.3. Per Person price model..... | 9 |
| 3.2.4. Per Person Request XML Parameters description | 11 |
| 3.2.5. Per Room or Unit price model..... | 14 |
| 3.2.6. Per Room XML Parameters description | 15 |
| 3.2.7. Per Occupancy price model | 17 |
| 3.2.8. Per Occupancy XML Parameters Description..... | 17 |
| 3.2.9. Per Room + Additional Price Model..... | 19 |

| | | |
|---------|---|----|
| 3.2.10. | Per Room with Extras Request XML Parameters Description | 20 |
| 3.2.11. | Successful response XML (Valid for all Price Models)..... | 20 |
| 3.2.12. | Error response XML (Valid for all Price Models) | 21 |
| 3.2.13. | Output XML parameter description..... | 21 |
| 3.2.14. | Stop Sales Functionality..... | 21 |
| 3.2.15. | Only Restrictions Update..... | 22 |
| 3.2.16. | Only Rates Update (without restrictions) | 22 |
| 3.3. | Booking Retrieval | 23 |
| 3.3.1. | Objective | 23 |
| 3.3.2. | Input request XML..... | 23 |
| 3.3.3. | Request XML Parameters description | 23 |
| 3.3.4. | Successful response XML with VCC details included..... | 24 |
| 3.3.5. | Successful response XML without VCC details included..... | 25 |
| 3.3.6. | Error response XML..... | 26 |
| 3.3.7. | Output XML parameter description..... | 26 |
| 4. | Definition of Child Rate Calculation | 30 |
| 5. | Notes..... | 31 |

1. Introduction

The aim of this document is to give the functions that an IT Channel Manager or provider partner have to implement in order to update rates, allotment, restrictions and retrieve the reservations from the FastPayHotels system.

The document assumes that the reader has a solid understanding of the electronic travel Distribution environment across business, commercial and technical terms, as well as a solid foundation in XML API deployments.

All requests are sent as **HTTP POST web requests** with http header:

Content-Type: text/xml; charset=utf-8 with **TLS1.2** encryption protocol. Responses are expected with the same content-type and charset.

The DateTime format should be in ISO yyyy-MM-dd for dates and yyyy-MM-ddTHH:mm:ss for datetime datafields.

Datetimes data fields are stored in UTC, therefore UTC datetimes should be used on requests whenever it's necessary.

A single service endpoint will be provided to access de service. The supplier is restricted to use the provided endpoint only.

This integration makes no use of soap protocol so Raw XML payload is used instead. Each method will use a different URL endpoint inside same service URL

Every request should contain the access credentials inside the user and password attributes and optionally Chain ID and/or HotelId when necessary (ChainCode and HotelCode in this document).

Is highly recommended supplier send Echo Token and Timestamp for ARI PUSH requests (availability/rates) even though no mandatory, for traceability reasons. Any support request related to ARI push will be turned down if no EchoToken / Timestamp is provided with the logs.

The abbreviated term "FPH" used in parameters descriptions, means Fastpayhotels.

2. Endpoint

2.1. Standard endpoint

<https://chm1.fastpayhotels.net/>

2.2. Custom endpoint

Channel manager provider could be requested to use custom endpoint URL at FastPayHotels' discretion to allow for better service performance management.

3. Methods

3.1. GetHotelInfo

<https://chm1.fastpayhotels.net/GetHotelInfo>

3.1.1. Objective

This function verifies if the login details are valid and pulls room types, rate plans and meal plans combinations existing in FastPayHotel's system from the connected properties.

Fastpayhotels will not use this to pull/retrieve the product information from the channel manager and therefore no new product (room types, rate plans or meal plans) can be created through this API

The Channel Manager should have already set up their system with the rooms, contracts or rate plans and meal plans that can be connected according to the commercial agreement with the hotelier.

FastPayHotels will not provide this information, so in case of any doubt about the rooms and rates to be created the provider should contact the hotelier.

The implementation of this function is mandatory since the hotel data is imported automatically to the mapping screen.

3.1.2. Prerequisites

User, password and (optionally) Chain Id and/or hotel code.

3.1.3. Sequence of events

- Input xml is sent into FastPayHotels' system.
- FastPayHotels validates the user against the credentials
- XML containing the room types and allowed occupancies, rate plans and meal plans is sent as response for a valid request and error message in case of authentication failure.

3.1.4. Input request XML

```
<?xml version="1.0" encoding="utf-8"?>
<GetHotelInfoRQ EchoToken="e1ea8122-a424-47f1-b3cf-e6762f741f6b" TimeStamp="2030-01-05" >
  <User>TestUser</User>
  <Password>TestPass</Password>
  <ChainCode>BUD-TE</ChainCode>
  <HotelCode>3403</HotelCode>
</GetHotelInfoRQ>
```

3.1.5. Request XML Parameters Description

| Element | Attribute | Type | Num | Description |
|-----------|-----------|--------|------|---|
| User | | String | 1 | Login Name |
| Password | | String | 1 | Login Password |
| ChainCode | | String | 0..1 | Chain code in FPH's System. If submitted, only hotels from selected Chain would be returned |
| HotelCode | | String | 0..1 | Hotel property Id in FPH's system. If not submitted, all hotels associated to the Chain (if ChainCode submitted) or associated to the user credentials would be returned. |

3.1.6. Successful response XML

```
<?xml version="1.0" encoding="utf-8"?>
<GetHotelInfoResponse>
<Hotels>
  <Hotel ChainCode="BUD-TE" Code="3403" Name="Test Hotel 1">
    <Rooms>
      <Room Code="1340" Description="Standard double" PriceType="Per Person">
        <Occupations>
          <MinNumberOfPersons>1</MinNumberOfPersons>
          <MaxNumberOfPersons>3</MaxNumberOfPersons>
          <MinNumberOfAdults>2</MinNumberOfAdults>
          <MaxNumberOfAdults>2</MaxNumberOfAdults>
          <MinNumberOfChildren>0</MinNumberOfChildren>
          <MaxNumberOfChildren>1</MaxNumberOfChildren>
        </Occupations>
        <RatePlans>
          <RatePlan Code="FLEX" Description="Flexible" CurrencyCode="EUR" RateType="Net"/>
          <RatePlan Code="NR" Description="Non Refundable" CurrencyCode="EUR" RateType="Net"/>
        </RatePlans>
        <MealPlans>
          <MealPlan Code="BB" Description="Bed And Breakfast"/>
          <MealPlan Code="HB" Description="Half Board"/>
        </MealPlans>
      </Room>
      <Room Code="1341" Description="1 Bedroom Apartment" PriceType="Per Room">
        <Occupations>
          <MinNumberOfPersons>2</MinNumberOfPersons>
          <MaxNumberOfPersons>4</MaxNumberOfPersons>
          <MinNumberOfAdults>2</MinNumberOfAdults>
          <MaxNumberOfAdults>2</MaxNumberOfAdults>
          <MinNumberOfChildren>0</MinNumberOfChildren>
          <MaxNumberOfChildren>2</MaxNumberOfChildren>
        </Occupations>
        <RatePlans>
          <RatePlan Code="FLEX" Description="Flexible" CurrencyCode="EUR" RateType="Net"/>
          <RatePlan Code="NR" Description="Non Refundable" CurrencyCode="EUR" RateType="Net"/>
        </RatePlans>
        <MealPlans>
          <MealPlan Code="RO" Description="Room Only"/>
        </MealPlans>
      </Room>
    </Rooms>
  </Hotel>
</GetHotelInfoResponse>
```

3.1.7. Error response XML

```
<?xml version="1.0" encoding="utf-8"?>
<GetHotelInfoResponse>
  <Errors>
    <Error Type="Wrong username or password"/>
  </Errors>
</GetHotelInfoResponse >
```

3.1.8. Output XML parameters description

| Element | Attribute | Type | Num | Description |
|---------------------|-------------|---------|------|---|
| Hotel | | | 1..n | |
| | ChainCode | String | 1 | Property chain code in FPH's system. It can be alphanumeric |
| | Code | String | 1 | Property Id in FPH's system |
| | Name | String | 1 | Property name |
| Room | | | 1..n | |
| | Code | String | 1 | Room type Id. It can be alphanumeric |
| | Description | String | 1 | Room name |
| | PriceType | String | 1 | This attribute informs the price model of the room. Possible values: Per Person: prices to be updated per person Per Room: prices to be updated per unit Per Room with Extras: Room rate for the base occupancy, and separately also send rates for additional guest outside the base occupancy Per Occupancy: Price to be updated per occupancy. |
| MinNumberOfPersons | | Integer | 1 | Minimum total occupancy of the room. |
| MaxNumberOfPersons | | Integer | 1 | Maximum total occupancy of the room. |
| MinNumberOfAdults | | Integer | 1 | Minimum number of adults allowed to stay at the room. |
| MaxNumberOfAdults | | Integer | 1 | Maximum number of adults allowed to stay at the room. |
| MinNumberOfChildren | | Integer | 1 | Minimum number of children allowed to stay at the room. |
| MaxNumberOfChildren | | Integer | 1 | Maximum number of children allowed to stay at the room. |

| | | | | |
|----------|--------------|--------|------|--|
| RatePlan | | | 1..n | |
| | Code | String | 1 | Rate code Id. It can be alphanumeric |
| | Description | String | 1 | Rate name |
| | CurrencyCode | String | 1 | ISO currency code of the Rate plan |
| | RateType | String | 1 | <p>This attribute informs the rate type so that the hotel knows how to set the rate while updating.</p> <p>Possible values:</p> <p>Gross = Gross rate. Not currently in use Fastpayhotels. ONLY use NET</p> <p>Net = Net rates. The updated price will not include the commission. This will be the price the hotel will invoice.</p> |
| MealPlan | | | 1 | |
| | Code | String | 1..N | <p>Meal plan code. It can be alphanumeric</p> <p>Channel must provide FastPayHotels the codes for MealPlans supported</p> <p>Default values would be:</p> <p>RO = Room Only BB = Bed and Breakfast HB = Half Board FB = Full Board AI = All Inclusive</p> |

3.2. HotelAvailRateUpdate

<https://chm1.fastpayhotels.net/HotelAvailRateUpdate>

3.2.1. Objective

This function is used to update rates, availability restrictions and inventory counts using the room, rate plan and meal plan codes obtained from a (previous) GetHotelInfo call.

3.2.2. Request XML

FastPayHotels supports multiple Chains per Channel so it is up to the channel manager to decide whether to use Chain Codes or not.

If it is agreed that Chain Codes will be used, they are mandatory on all requests.

Chain Codes must always be used if the Hotel Codes are not unique throughout the entire integration.

So, the Channel must ask “Will the codes for the hotels be unique throughout entire integration?”

- Yes - The chain code is optional, and can be used for reducing data transfer weight
- No - The chain code is mandatory on all requests

FastPayHotels CHM API supports up to four Price Models for provider product data, namely Price “Per Room/Unit”, “Per Pax/Per Person”, “Per Occupancy”, “Per Room + Additionals/Extras” which combines “Per Room + Per Person” models

Providers must send data in the same price model as indicated in a (previous) GetHotelInfo response per each Product Unit

Providers can choose from the following entity levels to set the Price Model:

- At Hotel level - All products in a given hotel use the same Price Model
- At RatePlan level - Different Price Models can be set for each defined rate plan
- At Room type level - Different Price Models can be set for each defined room type

Providers must send their data structure matching the selected Price Model configured in the inventory. No rate will be updated if the Price Model sent is different than the one configured (received in the GetHotelInfo response), nor will any data transformation be performed.

Providers can use their own mapping codes for the Price Model. Default values for the Price Types are:

- Prices per person → “Per Person”
- Prices per room → “Per Room”
- Prices per occupancy → “Per Occupancy”
- Prices per room + additional → “Per Room with Extras”

If custom codes are to be used, channel managers must inform them during the implementation phase to properly configure FastPayHotels’ system.

3.2.3 Per Person price model

For multiple occupancy allowance in a specific room.

This price model will update the price at person level (Pax type and order), from the base rate submitted in the *Adult* attribute up to a 7th adult, depending on the maximum capacity of the room.

```
<?xml version="1.0" encoding="utf-8"?>
<HotelAvailRateUpdateRQ
    xmlns:xsd="http://www.w3.org/2001/XMLSchema"
    xmlns: xsi="http://www.w3.org/2001/XMLSchema-instance"
    EchoToken="e1ea8122-a424-47f1-b3cf-e6762f741f6b"
    TimeStamp="2022-07-05T01:01:00" >
    <Credentials>
        <User>user</User>
        <Password>pass</Password>
    </Credentials>
    <HotelAvailRateMessages ChainCode="BUT-TU" HotelCode="14400">
        <HotelAvailRateMessage CurrencyCode="EUR" FromDate="2013-12-10" ToDate="2013-12-10"
        RoomCode="2222" RatePlanCode="FLEX">
            <RoomsToSell>115</RoomsToSell>
            <Release>2</Release>
            <MinimumStay>2</MinimumStay>
            <MaximumStay>0</MaximumStay>
            <Closed>False</Closed>
            <ClosedToArrival>False</ClosedToArrival>
            <ClosedToDeparture>False</ClosedToDeparture>
        </HotelAvailRateMessage>
    </HotelAvailRateMessages>
</HotelAvailRateUpdateRQ>
```

```

<Rates>
  <Rate MinStayBasedRate="1">
    <MealPlans>
      <MealPlan Code="BB">
        <Price PaxType="Adult" PaxPrice="59.00" AmountBeforeTax="50.00"/>
        <Price PaxType="SingleUse" PaxPrice="74.00" AmountBeforeTax="50.00"/>
        <Price PaxType="ThirdAdult" PaxPrice="44.25" AmountBeforeTax="50.00"/>
        <Price PaxType="FirstChildA" PaxPrice="0.00" AmountBeforeTax="50.00"/>
        <Price PaxType="FirstChildB" PaxPrice="44.25" AmountBeforeTax="50.00"/>
        <Price PaxType="SecondChildA" PaxPrice="29.50" AmountBeforeTax="50.00"/>
        <Price PaxType="SecondChildB" PaxPrice="29.50" AmountBeforeTax="50.00"/>
      </MealPlan>
      <MealPlan Code="HB">
        <Price PaxType="Adult" PaxPrice="69.00" AmountBeforeTax="50.00"/>
        <Price PaxType="SingleUse" PaxPrice="84.00" AmountBeforeTax="50.00"/>
        <Price PaxType="ThirdAdult" PaxPrice="51.75" AmountBeforeTax="50.00"/>
        <Price PaxType="FirstChildA" PaxPrice="0.00" AmountBeforeTax="50.00"/>
        <Price PaxType="FirstChildB" PaxPrice="51.75" AmountBeforeTax="50.00"/>
        <Price PaxType="SecondChildA" PaxPrice="34.50" AmountBeforeTax="50.00"/>
        <Price PaxType="SecondChildB" PaxPrice="34.50" AmountBeforeTax="50.00"/>
      </MealPlan>
      <MealPlan Code="HB">
        <Price PaxType="Adult" PaxPrice="69.00" AmountBeforeTax="50.00"/>
        <Price PaxType="SingleUse" PaxPrice="84.00" AmountBeforeTax="50.00"/>
        <Price PaxType="ThirdAdult" PaxPrice="51.75" AmountBeforeTax="50.00"/>
        <Price PaxType="FirstChildA" PaxPrice="0.00" AmountBeforeTax="50.00"/>
        <Price PaxType="FirstChildB" PaxPrice="51.75" AmountBeforeTax="50.00"/>
        <Price PaxType="SecondChildA" PaxPrice="34.50" AmountBeforeTax="50.00"/>
        <Price PaxType="SecondChildB" PaxPrice="34.50" AmountBeforeTax="50.00"/>
      </MealPlan>
    </MealPlans>
  </Rate>
</Rates>
</HotelAvailRateMessage>
<HotelAvailRateMessage CurrencyCode="EUR" FromDate="2013-12-11" ToDate="2013-12-11"
RoomCode="2222" RatePlanCode="FLEX">
  <RoomsToSell>114</RoomsToSell>
  <Release>2</Release>
  <MinimumStay>2</MinimumStay>
  <MaximumStay>0</MaximumStay>
  <Closed>False</Closed>
  <ClosedToArrival>False</ClosedToArrival>
  <ClosedToDeparture>False</ClosedToDeparture>
  <Rates>
    <Rate MinStayBasedRate="1">
      <MealPlans>
        <MealPlan Code="BB">
          <Price PaxType="Adult" PaxPrice="59.00" AmountBeforeTax="50.00"/>
          <Price PaxType="SingleUse" PaxPrice="74.00" AmountBeforeTax="50.00"/>
          <Price PaxType="ThirdAdult" PaxPrice="44.25" AmountBeforeTax="50.00"/>
          <Price PaxType="FirstChildA" PaxPrice="0.00" AmountBeforeTax="50.00"/>
          <Price PaxType="FirstChildB" PaxPrice="44.25" AmountBeforeTax="50.00"/>
          <Price PaxType="SecondChildA" PaxPrice="29.50" AmountBeforeTax="50.00"/>
          <Price PaxType="SecondChildB" PaxPrice="29.50" AmountBeforeTax="50.00"/>
        </MealPlan>
        <MealPlan Code="HB">
          <Price PaxType="Adult" PaxPrice="69.00" AmountBeforeTax="50.00"/>
          <Price PaxType="SingleUse" PaxPrice="84.00" AmountBeforeTax="50.00"/>
          <Price PaxType="ThirdAdult" PaxPrice="51.75" AmountBeforeTax="50.00"/>
          <Price PaxType="FirstChildA" PaxPrice="0.00" AmountBeforeTax="50.00"/>
          <Price PaxType="FirstChildB" PaxPrice="51.75" AmountBeforeTax="50.00"/>
          <Price PaxType="SecondChildA" PaxPrice="34.50" AmountBeforeTax="50.00"/>
          <Price PaxType="SecondChildB" PaxPrice="34.50" AmountBeforeTax="50.00"/>
        </MealPlan>
      </MealPlans>
    </Rate>
  </Rates>

```

3.2.4. Per Person Request XML Parameters description

| Element | Attribute | Type | Num | Description |
|------------------------|--------------|---------|------|---|
| User | | String | 1 | Login Name |
| Password | | String | 1 | Login Password |
| HotelAvailRateMessages | | | 1 | |
| | ChainCode | String | 0..1 | Chain code in FPH's system. Optional only if unique Hotel Codes are used |
| | HotelCode | String | 1 | Property Id in FPH's system. Always mandatory |
| HotelAvailRateMessage | | | 1..n | |
| | CurrencyCode | String | 1 | ISO currency code |
| | FromDate | Date | 1 | Start date. Format YYYY-MM-DD |
| | ToDate | Date | 1 | End date. Format YYYY-MM-DD |
| | RoomCode | String | 1 | Room type code |
| | RatePlanCode | String | 1 | Rate code |
| RoomsToSell | | Integer | 1 | Number of available units to be sold |
| Release | | Integer | 1 | Number of days of release (Min Booking Advanced Offset) |
| MinimumStay | | Integer | 1 | Minimum stay |
| MaximumStay | | Integer | 1 | Maximum stay |
| Closed | | String | 1 | Boolean. Stop sales indicator. Accepted values are: True = sales are closed for the submitted room and rate plan. False = sales are opened for the submitted room and rate. |
| ClosedToArrival | | String | 1 | Boolean. Closed to arrival indicator. Accepted values are: True = means that product is closed to arrival. False = means that product is open to arrival |

| | | | | |
|-------------------|------------------------|---------|-------|---|
| ClosedToDeparture | | String | 1 | Boolean. Closed to arrival indicator. Accepted values are: True = means that product is closed to arrival. False = means that product is open to arrival |
| Rates | | | 1 | |
| Rate | | | 1.. n | |
| | MinStayBasedRate | Integer | 0..1 | There will always be a Rate element with MinStayBasedRate=1 as this is the default mandatory value. Stay indicator. If the hotel has a different price depending on the number of days of the stay this element can be used to submit a different price without the need of creating a new RatePlanCode. |
| MealPlans | | | 1 | |
| MealPlan | | | 1..5 | |
| | Code | String | 1 | Meal plan code. Mandatory field. The accepted values are: RO = Room Only BB = Bed and Breakfast HB = Half Board FB = Full Board AI = All Inclusive |
| Price | PaxType=" Adult" | Integer | 1 | When price model is per person the price is submitted per each of the persons allowed in the room. PaxType="Adult" would be the price for 1 adult or Adults inside the room base/standard occupancy |
| Price | PaxType=" SecondAdult" | Integer | 1 | Price for the second adult if Adult value is not considered inside a multiple base/standard occupancy |

| | | | | |
|-------|------------------------|---------|------|--|
| Price | PaxType="SingleUse" | Integer | 0..1 | Price in single occupancy when the 2 adults' occupancy is also possible. If only single occupancy is allowed, then only the "Adult" tag will be used. |
| Price | PaxType="ThirdAdult" | Integer | 0..1 | Price of the 3rd adult |
| Price | PaxType="FourthAdult" | Integer | 0..1 | Price of the 4th adult |
| Price | PaxType="FifthAdult" | Integer | 0..1 | Price of the 5th adult |
| Price | PaxType="SixthAdult" | Integer | 0..1 | Price of the 6th adult |
| Price | PaxType="SeventhAdult" | Integer | 0..1 | Price of the 7th adult |
| Price | PaxType="FirstChildA" | Integer | 0..1 | Price of the 1st child of the 1st age range. |
| Price | PaxType="FirstChildB" | Integer | 0..1 | Price of the 1st child of the 2nd age range. |
| Price | PaxType="SecondChildA" | Integer | 0..1 | Price of the 2nd child of the 1st age range |
| Price | PaxType="SecondChildB" | Integer | 0..1 | Price of the 2nd child of the 2nd age range |
| Price | PaxType="ThirdChildA" | Integer | 0..1 | Price of the 3rd child of the 1st age range |
| Price | PaxType="ThirdChildB" | Integer | 0..1 | Price of the 3rd child of the 2nd age range |
| Price | PaxType="FourthChildA" | Integer | 0..1 | Price of the 4th child of the 1st age range |
| Price | PaxType="FourthChildB" | Integer | 0..1 | Price of the 4th child of the 2nd age range |
| Price | PaxType="FifthChildA" | Integer | 0..1 | Price of the 5th child of the 1st age range |
| Price | PaxType="FifthChildB" | Integer | 0..1 | Price of the 5th child of the 2nd age range |
| | | | | In this Price Model, the only PaxType allowed are up to 7 adults, and/or 5 children. Any sequence consecutive to those mentioned above will not be processed. |

3.2.5. Per Room or Unit price model

For multiple occupancy allowance in a specific room, having all a global unique same price.

This price model will update the price at room type OR rate plan level depending on the inventory configuration* a unique price regardless the accepted occupancies in the room.

If price model is assigned to “Rate Plan”, all rooms will use that given Price Model for rates in that Rate Plan

If price model is assigned to “Room Type”, that room price model will be the same for each Rate Plan.

*FastPayHotels currently does not support Price Mode configuration at Product Level (RatePlan + Room Type combo)

```
<?xml version="1.0" encoding="utf-8"?>
<HotelAvailRateUpdateRQ
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  EchoToken="e1ea8122-a424-47f1-b3cf-e6762f741f6b" TimeStamp="2022-07-05T01:01:00"
  <Credentials>
    <User>user</User>
    <Password>password</Password>
  </Credentials>
  <HotelAvailRateMessages ChainCode="BUT-TU" HotelCode="14400">
    <HotelAvailRateMessage CurrencyCode="EUR" FromDate="2013-11-28" ToDate="2013-11-28" RoomCode="3333" RatePlanCode="NR">
      <RoomsToSell>0</RoomsToSell>
      <Release>1</Release>
      <MinimumStay>2</MinimumStay>
      <MaximumStay>0</MaximumStay>
      <Closed>True</Closed>
      <ClosedToArrival>False</ClosedToArrival>
      <ClosedToDeparture>False</ClosedToDeparture>
      <Rates>
        <Rate MinStayBasedRate="1">
          <MealPlans>
            <MealPlan Code="BB">
              <Price RoomPrice="193.00" AmountBeforeTax="50.00"/>
            </MealPlan>
            <MealPlan Code="HB">
              <Price RoomPrice="216.00" AmountBeforeTax="50.00"/>
            </MealPlan>
          </MealPlans>
        </Rate>
      </Rates>
    </HotelAvailRateMessage>
    <HotelAvailRateMessage CurrencyCode="EUR" FromDate="2013-11-29" ToDate="2013-12-04" RoomCode="3333" RatePlanCode="NR">
      <RoomsToSell>550</RoomsToSell>
      <Release>1</Release>
      <MinimumStay>2</MinimumStay>
      <MaximumStay>0</MaximumStay>
      <Closed>False</Closed>
      <Rates>
        <Rate MinStayBasedRate="1">
          <MealPlans>
            <MealPlan Code="BB">
              <Price RoomPrice="193.00" AmountBeforeTax="50.00"/>
            </MealPlan>
            <MealPlan Code="HB">
              <Price RoomPrice="216.00" AmountBeforeTax="50.00"/>
            </MealPlan>
          </MealPlans>
        </Rate>
      </Rates>
    </HotelAvailRateMessage>
  </HotelAvailRateMessages>
</HotelAvailRateUpdateRQ>
```

3.2.6. Per Room XML Parameters Description

| Element | Attribute | Type | Num | Description |
|------------------------|--------------|---------|------|---|
| User | | String | 1 | Login Name |
| Password | | String | 1 | Login Password |
| HotelAvailRateMessages | | | 1 | |
| | ChainCode | String | 0..1 | Chain code in FPH's system. Optional only if unique Hotel Codes are used |
| | HotelCode | String | 1 | Property Id in FPH's system. Always mandatory |
| HotelAvailRateMessage | | | 1..n | |
| | CurrencyCode | String | 1 | ISO currency code |
| | FromDate | Date | 1 | Start date. Format YYYY-MM-DD |
| | ToDate | Date | 1 | End date. Format YYYY-MM-DD |
| | RoomCode | String | 1 | Room type code |
| | RatePlanCode | String | 1 | Rate code |
| RoomsToSell | | Integer | 1 | Number of available units to be sold |
| Release | | Integer | 1 | Number of days of release (Min Booking Advanced Offset) |
| MinimumStay | | Integer | 1 | Minimum stay |
| MaximumStay | | Integer | 1 | Maximum stay |
| Closed | | String | 1 | Boolean. Stop sales indicator. Accepted values are: True = sales are closed for the submitted room and rate plan. False = sales are opened for the submitted room and rate. |
| ClosedToArrival | | String | 1 | Boolean. Closed to arrival indicator. Accepted values are: True = means that product is closed to arrival. False = means that product is open to arrival |

| | | | | |
|-------------------|------------------|---------|-------|---|
| ClosedToDeparture | | String | 1 | Boolean. Closed to arrival indicator. Accepted values are: True = means that product is closed to arrival. False = means that product is open to arrival |
| Rates | | | 1 | |
| Rate | | | 1.. n | |
| | MinStayBasedRate | Integer | 0..1 | There will always be a Rate element with MinStayBasedRate=1 as this is the default mandatory value. Stay indicator. If the hotel has a different price depending on the number of days of the stay this element can be used to submit a different price without the need of creating a new RatePlanCode. |
| MealPlans | | | 1 | |
| MealPlan | | | 1..5 | |
| | Code | | 1 | Meal plan code. Mandatory field. The accepted values are: RO = Room Only BB = Bed and Breakfast HB = Half Board FB = Full Board AI = All Inclusive |
| Price | RoomPrice | | 0..1 | Mandatory when price model is per unit, the submitted price would be for the whole room, regardless the number of persons allowed to stay in. This model is usually used when each room allows a unique occupancy. |

| | | | | |
|-------|-----------------|--|------|--|
| Price | AmountBeforeTax | | 0..1 | Price before taxes. This node is the same regardless the price model |
|-------|-----------------|--|------|--|

3.2.7. Per Occupancy price model

For unique price per occupancy allowance in a specific room.

This price model will update the price at occupancy level, the price for all adult + children combinations accepted.

```
<?xml version="1.0" encoding="utf-8"?>
<HotelAvailRateUpdateRQ
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  EchoToken="e1ea8122-a424-47f1-b3cf-e6762f741f6b"
 TimeStamp="2022-07-05T01:01:00" >

  <Credentials>
    <User>user</User>
    <Password>password</Password>
  </Credentials>
  <HotelAvailRateMessages ChainCode="BUT-TU" HotelCode="14400">
    <HotelAvailRateMessage CurrencyCode="EUR" FromDate="2013-12-08" ToDate="2013-12-17"
RoomCode="4444" RatePlanCode="FLEX">
      <RoomsToSell>390</RoomsToSell>
      <Release>0</Release>
      <MinimumStay>3</MinimumStay>
      <MaximumStay>0</MaximumStay>
      <Closed>False</Closed>
      <ClosedToArrival>False</ClosedToArrival>
      <ClosedToDeparture>False</ClosedToDeparture>
    <Rates>
      <Rate MinStayBasedRate="1">
        <MealPlans>
          <MealPlan Code="BB">
            <Price OccupancyPrice="80.00" Adults="1" Children="0" AmountBeforeTax="70.00"/>
            <Price OccupancyPrice="86.00" Adults="2" Children="0" AmountBeforeTax="70.00"/>
            <Price OccupancyPrice="90.50" Adults="2" Children="1" AmountBeforeTax="70.00"/>
            <Price OccupancyPrice="90.50" Adults="3" Children="0" AmountBeforeTax="70.00"/>
          </MealPlan>
          <MealPlan Code="HB">
            <Price OccupancyPrice="90.00" Adults="1" Children="0" AmountBeforeTax="70.00"/>
            <Price OccupancyPrice="106.00" Adults="2" Children="0" AmountBeforeTax="70.00"/>
            <Price OccupancyPrice="118.00" Adults="2" Children="1" AmountBeforeTax="70.00"/>
            <Price OccupancyPrice="118.00" Adults="3" Children="0" AmountBeforeTax="70.00"/>
          </MealPlan>
        </MealPlans>
      </Rate>
    </Rates>
  </HotelAvailRateMessage>
</HotelAvailRateMessages>
</HotelAvailRateUpdateRQ>
```

3.2.8. Per Occupancy XML Parameters Description

| Element | Attribute | Type | Num | Description |
|------------------------|------------------|-------------|------------|---|
| User | | String | 1 | Login Name |
| Password | | String | 1 | Login Password |
| HotelAvailRateMessages | | | 1 | |
| | ChainCode | String | 0..1 | Chain code in FPH's system. Optional only if unique Hotel Codes are used |
| | HotelCode | String | 1 | Property Id in FPH's system. Always mandatory |
| HotelAvailRateMessage | | | 1..n | |
| | CurrencyCode | String | 1 | ISO currency code |
| | FromDate | Date | 1 | Start date. Format YYYY-MM-DD |
| | ToDate | Date | 1 | End date. Format YYYY-MM-DD |
| | RoomCode | String | 1 | Room type code |
| | RatePlanCode | String | 1 | Rate code |
| RoomsToSell | | Integer | 1 | Number of available units to be sold |
| Release | | Integer | 1 | Number of days of release (Min Booking Advanced Offset) |
| MinimumStay | | Integer | 1 | Minimum stay |
| MaximumStay | | Integer | 1 | Maximum stay |
| Closed | | String | 1 | Boolean. Stop sales indicator. Accepted values are: True = sales are closed for the submitted room and rate plan. False = sales are opened for the submitted room and rate. |
| ClosedToArrival | | String | 1 | Boolean. Closed to arrival indicator. Accepted values are: True = means that product is closed to arrival. False = means that product is open to arrival |

| | | | | |
|-------------------|------------------|---------|-------|---|
| ClosedToDeparture | | String | 1 | Boolean. Closed to arrival indicator. Accepted values are: True = means that product is closed to arrival. False = means that product is open to arrival |
| Rates | | | 1 | |
| Rate | | | 1.. n | |
| | MinStayBasedRate | Integer | 0..1 | There will always be a Rate element with MinStayBasedRate=1 as this is the default mandatory value. Stay indicator. If the hotel has a different price depending on the number of days of the stay this element can be used to submit a different price without the need of creating a new RatePlanCode. |
| MealPlans | | | 1 | |
| MealPlan | | | 1..5 | |
| | Code | | 1 | Meal plan code. Mandatory field. The accepted values are: RO = Room Only BB = Bed and Breakfast HB = Half Board FB = Full Board AI = All Inclusive |
| Price | OccupancyPrice | | 0..1 | Mandatory when price model is peroccupancy, the price of each adults + children combination allowed to stay in the room should be submitted. |
| Price | AmountBeforeTax | | 0..1 | Amount before taxes |

3.2.9. Per Room + Additional price model

For multiple occupancy allowance in a specific room, having all a global unique same price.

This price model will use when the property sends a Room rate for the base occupancy, and separately also send rates for additional guest outside the base occupancy. In this case the Room Rate will be valid for all the occupancies allowed in the base occupancy.

The Base Occupancy configuration must be given to Fastpayhotels implementation team in advance.

If price model is assigned to “Rate Plan”, all rooms will use that given Price Model for rates in that Rate Plan

If price model is assigned to “Room Type”, that room price model will be the same for each Rate Plan.

*FastPayHotels currently does not support Price Mode configuration at Product Level (RatePlan + Room Type combo)

```
<?xml version="1.0" encoding="utf-8"?>
<HotelAvailRateUpdateRQ
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  EchoToken="e1ea8122-a424-47f1-b3cf-e6762f741f6b" TimeStamp="2022-07-05T01:01:00" >
  <Credentials>
    <User>user</User>
    <Password>password</Password>
  </Credentials>
  <HotelAvailRateMessages ChainCode="BUT-TU" HotelCode="14400">
    <HotelAvailRateMessage CurrencyCode="EUR" FromDate="2013-12-08" ToDate="2013-12-17"
      RoomCode="4444" RatePlanCode="FLEX">
      <RoomsToSell>390</RoomsToSell>
      <Release>0</Release>
      <MinimumStay>3</MinimumStay>
      <MaximumStay>0</MaximumStay>
      <Closed>False</Closed>
      <ClosedToArrival>False</ClosedToArrival>
      <ClosedToDeparture>False</ClosedToDeparture>
      <Rates>
        <Rate MinStayBasedRate="1">
          <MealPlans>
            <MealPlan Code="BB">
              <Price RoomPrice="259.00"/>
              <Price PaxType="ThirdAdult" PaxPrice="44.25" AmountBeforeTax="44.25"/>
              <Price PaxType="FirstChildA" PaxPrice="0.00" AmountBeforeTax="44.25"/>
              <Price PaxType="FirstChildB" PaxPrice="44.25" AmountBeforeTax="44.25"/>
              <Price PaxType="SecondChildA" PaxPrice="29.50" AmountBeforeTax="44.25"/>
              <Price PaxType="SecondChildB" PaxPrice="29.50" AmountBeforeTax="44.25"/>
            </MealPlan>
            <MealPlan Code="HB">
              <Price RoomPrice="289.00"/>
              <Price PaxType="ThirdAdult" PaxPrice="51.75" AmountBeforeTax="44.25"/>
              <Price PaxType="FirstChildA" PaxPrice="0.00" AmountBeforeTax="44.25"/>
              <Price PaxType="FirstChildB" PaxPrice="51.75" AmountBeforeTax="44.25"/>
              <Price PaxType="SecondChildB" PaxPrice="29.50" AmountBeforeTax="44.25"/>
            </MealPlan>
          </MealPlans>
        </Rate>
      </Rates>
    </HotelAvailRateMessage>
  </HotelAvailRateMessages>
</HotelAvailRateUpdateRQ>
```

*On the above example, the base occupancy or the room price will be 2 adults, so the additional

3.2.10. Per Room with Extras Request XML Parameters description

View Per Room and Per Person parameters description

3.2.11. Successful response XML (Valid for all Price Models)

```
<?xml version="1.0" encoding="utf-8"?>
<HotelAvailRateUpdateRS
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-
  instance">
  <Success/>
</HotelAvailRateUpdateRS>
```

3.2.12. Error response XML (Valid for all Price Models)

```
<?xml version="1.0" encoding="utf-8"?>
<HotelAvailRateUpdateRS
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <Errors>
    <Error Type="Invalid Room or Rate Code"/>
  </Errors>
</HotelAvailRateUpdateRS>
```

3.2.13. Output XML parameter description

| Element | Attribute | Type | Num | Description |
|---------|-----------|--------|------|---|
| Success | | | 0..1 | The Success element denotes the update has been acknowledged. |
| Error | Type | String | 0..n | The Error element denotes the update has not been acknowledged due to any failure. The error description can be detailed in the Error Type attribute. |

3.2.14. Stop Sales Functionality

The default application of a stop sales is by hotel, room and rate plan. The Closed tag is sent at the HotelAvailRateMessage element level.

Example

A stop sale for room DBL and rateplan FLEX is updated as follows:

```
<?xml version="1.0" encoding="utf-8"?>
<HotelAvailRateMessage CurrencyCode="EUR" FromDate="2017-11-30" ToDate="2017-11-30"
RoomCode="DBL" RatePlanCode="FLEX">
  <RoomsToSell>318</RoomsToSell>
  <Release>1</Release>
  <MinimumStay>1</MinimumStay>
  <MaximumStay>0</MaximumStay>
  <Closed>True</Closed>
  <Rates>
    <Rate MinStayBasedRate="1">
      <MealPlans>
        <MealPlan Code="RO">
          <Price PaxPrice="48.15" PaxType="Adult"/>
          <Price PaxPrice="33.71" PaxType="ThirdAdult"/>
        </MealPlan>
        <MealPlan Code="BB">
          <Price PaxPrice="57.78" PaxType="Adult"/>
          <Price PaxPrice="40.45" PaxType="ThirdAdult"/>
        </MealPlan>
      </MealPlans>
    </Rate>
  </Rates>
</HotelAvailRateMessage>
```

3.2.15. Only Restrictions Update

The default application to only send updates for Restrictions is by hotel, room and rate plan. All meal plans will be updated to that specific new input. To apply restrictions by specific meal plan, Rates parameters must be included in the message.

Example

```
<?xml version="1.0" encoding="utf-8"?>
<HotelAvailRateUpdateRQ
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  EchoToken="e1ea8122-a424-47f1-b3cf-e6762f741f6b"
  TimeStamp="2022-07-05T01:01:00" >
  <Credentials>
    <User>user</User>
    <Password>password</Password>
  </Credentials>
  <HotelAvailRateMessages ChainCode="BUT-TU" HotelCode="14400">
    <HotelAvailRateMessage CurrencyCode="EUR" FromDate="2013-12-08" ToDate="2013-12-17"
    RoomCode="4444" RatePlanCode="FLEX">
      <RoomsToSell>10</RoomsToSell>
      <Release>1</Release>
      <MinimumStay>3</MinimumStay>
      <MaximumStay>0</MaximumStay>
      <Closed>True</Closed>
      <ClosedToArrival>False</ClosedToArrival>
      <ClosedToDeparture>False</ClosedToDeparture>
    </HotelAvailRateMessage>
  </HotelAvailRateMessages>
</HotelAvailRateUpdateRQ>
```

3.2.16. Only Rates Update (without restrictions)

The default application to only send updates for Rates is by hotel, room, rate plan and meal plan.

```
<HotelAvailRateUpdateRQ xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  EchoToken="e1ea8122-a424-47f1-b3cf-e6762f741f6b" TimeStamp="2022-07-
  05T01:01:00" >
  <Credentials>
```

```

<User>user</User>
<Password>password</Password>
</Credentials>
<HotelAvailRateMessages ChainCode="BUT-TU" HotelCode="14400">
    <HotelAvailRateMessage CurrencyCode="EUR" FromDate="2013-12-08" ToDate="2013-12-17" RoomCode="4444" RatePlanCode="FLEX">
        <Rates>
            <Rate MinStayBasedRate="1">
                <MealPlans>
                    <MealPlan Code="BB">
                        <Price RoomPrice="259.00"/>
                        <Price PaxType="ThirdAdult" PaxPrice="44.25"/>
                        <Price PaxType="FirstChildA" PaxPrice="0.00"/>
                        <Price PaxType="FirstChildB" PaxPrice="44.25"/>
                        <Price PaxType="SecondChildA" PaxPrice="29.50"/>
                        <Price PaxType="SecondChildB" PaxPrice="29.50"/>
                    </MealPlan>
                    <MealPlan Code="HB">
                        <Price RoomPrice="289.00"/>
                        <Price PaxType="ThirdAdult" PaxPrice="51.75"/>
                        <Price PaxType="FirstChildA" PaxPrice="0.00"/>
                        <Price PaxType="FirstChildB" PaxPrice="51.75"/>
                        <Price PaxType="SecondChildB" PaxPrice="29.50"/>
                    </MealPlan>
                </MealPlans>
            </Rate>
        </Rates>
    </HotelAvailRateMessage>
</HotelAvailRateMessages>
</HotelAvailRateUpdateRQ>

```

3.3. Booking Retrieval

<https://chm1.fastpayhotels.net/BookingRetrieval>

3.3.1. Objective

This function is used to fetch the sold bookings within the submitted period.

Only last status of reservations is expected. We do not support booking modifications. Will be as canceled and rebook.

We will only send one room per booking. No multiroom booking is supported.

The Cancelled status should only be returned when all the rooms from a reservation are cancelled.

UTC time to be used when retrieving a booking.

3.3.2. Input request XML

```

<?xml version="1.0" encoding="utf-8"?>
<BookingRetrievalRQ>
<User>user</User>
<Password>password</Password>
<ChainCode>BUT-TU</ChainCode>
<HotelCode>3403</HotelCode>
<ReservationID/>
<ModifiedDateFrom>2013-12-01 00:00:00</ModifiedDateFrom>
<ModifiedDateTo>2013-12-07 17:07:19</ModifiedDateTo>
</BookingRetrievalRQ>

```

3.3.3. Request XML Parameters description

| Element | Attribute | Type | Num | Description |
|------------------|------------------|-------------|------------|--|
| User | | String | 1 | Login Name |
| Password | | String | 1 | Login Password |
| ChainCode | | String | 0..1 | Chain code on FPH's system. Optional only if unique Hotel Codes are used |
| HotelCode | | String | 0..1 | Property Id in FPH's system. Required whenever Chaincode is not supplied. |
| ReservationID | | String | 0..1 | Reservation locator. If submitted, only the reservation with this reservation Id should be returned. |
| ModifiedDateFrom | | String | 1 | Valid Last modification Date From. Format: YYYY-MM-DD 00:00:00 (UTC) |
| ModifiedDateTo | | String | 1 | Valid Last modification Date To. Format: YYYY-MM-DD 00:00:00 (UTC) |

3.3.4. Successful response XML with VCC details included

```

<?xml version="1.0" encoding="utf-8"?>
<BookingRetrievalResponse responseDate="2022-11-03T15:06:21Z" xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <HotelReservations>
    <HotelReservation ResStatus="Confirmed" ChainCode=" BUT-TU " HotelCode="3403" HotelName="TEST Hotel"
      BookingDate="2022-08-17T10:18:51.39" LastModifyDateTime="2022-10-24T12:28:50.537" CheckinDate="2022-10-25"
      CheckOutDate="2022-10-26">
      <Rooms>
        <Room CheckinDate="2022-10-25" CheckOutDate="2022-10-26" RoomCode="DBL2" RoomDescription="Double Room"
          MealPlanCode="BB" MealPlanDescription="BED & BREAKFAST" RatePlanCode="FLEX" RatePlanDescription="Flexible"
          NumberOfGuests="2" NumberOfAdults="2" NumberOfChildren="0" NumberOfBabies="0">
          <Guests>
            <Guest GivenName="TEST BOOKING FASTPAYHOTELS" SurName="TEST BOOKING FASTPAYHOTELS" Age="30"
              PaxType="A"/>
            <Guest GivenName="TEST BOOKING FASTPAYHOTELS" SurName="TEST BOOKING FASTPAYHOTELS" Age="30"
              PaxType="A"/>
          </Guests>
          <Pricing>
            <DailyRates>
              <DailyRate EffectiveDate="2022-10-25">
                <Total AmountAfterTax="96.59" AmountBeforeTax="86.59" CurrencyCode="EUR" IsNetRate="false"
                  IsGrossRate="false" Commission="0"/>
                </DailyRate>
              </DailyRates>
              <RoomTotals>
                <RoomTotal AmountAfterTax="96.59" AmountBeforeTax="86.59" CurrencyCode="EUR" IsNetRate="true"
                  IsGrossRate="false" Commission="0"/>
              </RoomTotals>
            </Pricing>
          </Room>
        </Rooms>
        <SpecialRequests>
          <SpecialRequest>
            <Text>TEST BOOKING FASTPAYHOTELS.</Text>
          </SpecialRequest>
        </SpecialRequests>
      </Room>
    </HotelReservation>
  </HotelReservations>
</BookingRetrievalResponse>

```

```

</SpecialRequest>
</SpecialRequests>
<ReservationInfo>
    <Total AmountAfterTax="96.59" AmountBeforeTax="86.59" CurrencyCode="EUR" IsNetRate="true" IsGrossRate="false">
        Commission="0"/>
        <Customer>
            <LeadPax GivenName="TEST BOOKING FASTPAYHOTELS" SurName="TEST BOOKING FASTPAYHOTELS"/>
            <PaymentForm>
                <PaymentCard CVV="" CardType="MC" CardNumber="1111222233334444" ExpireDate="2024-02-25">
                    <CardHolderName>FASTPAY HOTELS</CardHolderName>
                </PaymentCard>
            </PaymentForm>
            <Contact>
                <Telephone/>
                <Email/>
            </Contact>
        </Customer>
        <ReservationIDs>
            <ReservationID Value="FPHH91252X6"/>
        </ReservationIDs>
    </ReservationInfo>
</HotelReservation>

```

3.3.5. Successful response XML without VCC details included

```

<?xml version="1.0" encoding="utf-8"?>
<BookingRetrievalResponse responseDate="2022-11-03T15:06:21Z" xmlns:xsd="http://www.w3.org/2001/XMLSchema"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
    <HotelReservations>
        <HotelReservation ResStatus="Reserved" ChainCode=" BUT-TU " HotelCode="3403" HotelName="TEST Hotel"
            BookingDate="2022-08-17T10:18:51.39" LastModifyDateTime="2022-10-24T12:28:50.537" CheckinDate="2022-10-25"
            CheckOutDate="2022-10-26">
            <Rooms>
                <Room CheckinDate="2022-10-25" CheckOutDate="2022-10-26" RoomCode="DBL2" RoomDescription="Double Room"
                    MealPlanCode="BB" MealPlanDescription="BED & BREAKFAST" RatePlanCode="FLEX" RatePlanDescription="Flexible"
                    NumberOfGuests="2" NumberOfAdults="2" NumberOfChildren="0" NumberOfBabies="0">
                    <Guests>
                        <Guest GivenName="TEST BOOKING FASTPAYHOTELS" SurName="TEST BOOKING FASTPAYHOTELS" Age="30"
                            PaxType="A"/>
                        <Guest GivenName="TEST BOOKING FASTPAYHOTELS" SurName="TEST BOOKING FASTPAYHOTELS" Age="30"
                            PaxType="A"/>
                    </Guests>
                    <Pricing>
                        <DailyRates>
                            <DailyRate EffectiveDate="2022-10-25">
                                <Total AmountAfterTax="96.59" AmountBeforeTax="86.59" CurrencyCode="EUR" IsNetRate="false"
                                    IsGrossRate="false" Commission="0"/>
                                </DailyRate>
                            </DailyRates>
                            <RoomTotals>
                                <RoomTotal AmountAfterTax="96.59" AmountBeforeTax="86.59" CurrencyCode="EUR" IsNetRate="true"
                                    IsGrossRate="false" Commission="0"/>
                            </RoomTotals>
                        </Pricing>
                    </Room>
                </Rooms>
                <SpecialRequests>
                    <SpecialRequest>

```

```

<Text>TEST BOOKING FASTPAYHOTELS.</Text>
</SpecialRequest>
</SpecialRequests>
<ReservationInfo>
    <Total AmountAfterTax="96.59" AmountBeforeTax="86.59" CurrencyCode="EUR" IsNetRate="true" IsGrossRate="false"
Commission="0"/>
    <Customer>
        <LeadPax GivenName="TEST BOOKING FASTPAYHOTELS" SurName="TEST BOOKING FASTPAYHOTELS"/>
        <PaymentForm>
            <PaymentCard CardType="" CardNumber="" ExpireDate="">
                <CardHolderName> </CardHolderName>
            </PaymentCard>
        </PaymentForm>
        <Contact>
            <Telephone/>
            <Email/>
        </Contact>
    </Customer>
    <ReservationIDs>
        <ReservationID Value="FPHH91252X6"/>
    </ReservationIDs>
</ReservationInfo>
</HotelReservation>

```

Expected response when there are no existing reservations attending to the requesting criteria.

```

<?xml version="1.0" encoding="UTF-8"?>
<BookingRetrievalResponse responseDate="2012-12-19T10:52:25.687">
    <HotelReservations>
    </HotelReservations>
</BookingRetrievalResponse>

```

3.3.6. Error response XML

```

<?xml version="1.0" encoding="UTF-8"?>
<BookingRetrievalResponse responseDate="2012-12-19T10:52:25.687">
    <Errors>
        <Error Type="Hotel code not found"/>
    </Errors>
</BookingRetrievalResponse>

```

3.3.7. Output XML parameter description

| Element | Attribute | Type | Num | Description |
|--------------------------|------------------|-------------|------------|----------------------------------|
| BookingRetrievalResponse | | | 1 | |
| | ResponseDate | DateTime | 1 | Date and UTC time of the request |
| HotelReservations | | | 1 | |
| HotelReservation | | | 1..n | |

| | | | | |
|-------|---------------------|----------|------|---|
| | ResStatus | String | 1 | Status of the reservation. Possible values: Reserved : Reservation is active and has not been modified. Cancelled : Reservation is cancelled. |
| | ChainCode | String | 1 | Property chain code in FPH's system |
| | HotelCode | String | 1 | Property Id |
| | HotelName | String | 1 | Name of the hotel |
| | BookingDate | DateTime | 1 | Booking date |
| | LastModifyDateTime | DateTime | 1 | Last modification date. When Status=Reserved this date should also be the booking date. When Status=Amended this date is the modification date. When Status=Cancelled this date is acknowledged as the cancellation date. |
| | CheckinDate | Date | 1 | Reservation's date of arrival |
| | CheckOutDate | Date | 1 | Reservations' date of departure |
| Rooms | | | 1 | |
| Room | | | 1..n | |
| | CheckinDate | Date | 1 | Date of arrival of the room |
| | CheckOutDate | Date | 1 | Date of departure of the room |
| | RoomCode | String | 1 | Room type Id |
| | RoomDescription | String | 1 | Name of the room |
| | MealPlanCode | String | 1 | Meal plan code. The accepted values are: RO = Room Only BB = Bed and Breakfast HB = Half Board FB = Full Board AI = All Inclusive |
| | MealPlanDescription | String | 1 | Meal plan name |
| | RatePlanCode | String | 1 | Rate code |
| | RatePlanDescription | String | 1 | Name of the rate |

| | | | | |
|------------|------------------|---------|------|---|
| | NumberOfGuests | Integer | 1 | Total number of persons to stay in the room |
| | NumberOfAdults | Integer | 1 | Number of adults to stay in the room |
| | NumberOfChildren | Integer | 1 | Number of children to stay in the room |
| | NumberOfBabies | Integer | 1 | Number of babies to stay in the room |
| Guests | | | 1 | |
| Guest | | | 1..n | The number of Guest. Elements provided at the Guests array must match the value of the NumberOfGuests attribute. If only one occupant name can be provided, please repeat the same name for all occupants or provide dummy names like "adult2", "adult3", "child1", "child2," ... |
| | Title | String | 0..1 | Title of the guest |
| | Given Name | String | 1 | Name of the guest |
| | SurName | String | 1 | Surname of the guest |
| | Age | Integer | 1 | Guest's age |
| | PaxType | String | 1 | Pax type identifier. Accepted values are: A = Adult C = Child B = Baby |
| Pricing | | | 1 | |
| DailyRates | | | 1 | |
| DailyRate | | | 1..n | |
| | EffectiveDate | Date | 1 | Daily break down of the applied rates |
| | CurrencyCode | String | 1 | ISO currency code |
| RoomTotals | | | 1..n | |
| RoomTotal | | | 1 | |
| | AmountAfterTax | Decimal | 1 | Total room price |
| | AmountBeforeTax | Decimal | 0..1 | Total room price before taxes |
| | CurrencyCode | String | 1 | ISO currency code |

| | | | | |
|-----------------|-----------------|---------|------|---|
| | IsNetRate | boolean | 1 | Net rate indicator. Denotes the cost should be acknowledged as a net price. |
| | IsGrossRate | boolean | 1 | Gross rate indicator. Denotes the cost should be acknowledged as a gross price. |
| | Commission | String | 0..1 | Commission amount. Not In Use by FPH If IsGrossRate=true, the applied commission must be informed. |
| SpecialRequests | | | 0..1 | |
| SpecialRequest | | | 0..1 | Remarks container |
| | Text | String | 1..n | Remarks requested by the customer |
| ReservationInfo | | | | |
| Total | AmountAfterTax | Integer | 1 | Total price of the reservation |
| | AmountBeforeTax | Decimal | 0..1 | Total reservation price before taxes. Optional |
| | CurrencyCode | String | 1 | ISO currency code |
| | IsNetRate | boolean | 1 | Net rate indicator. Denotes the cost should be acknowledged as a net price. |
| | IsGrossRate | boolean | 1 | Gross rate indicator. Denotes the cost should be acknowledged as a gross price. |
| | Commission | String | 0..1 | Commission amount. If IsGrossRate=true, the applied commission must be informed. |
| Customer | | | 1 | |
| LeadPax | | | 1 | |
| | GivenName | | 1 | Name of the head of the group for the reservation. If the names of all passengers can't be broken down in the Guest element, at least the lead pax name should be informed. |
| | SurName | | 1 | Surname of the lead pax |

| | | | | |
|--------------------|----------------|---------|------|---|
| PaymentForm | | | 0..1 | |
| PaymentCard | | | | |
| | CardType | String | 0..1 | OTA Card type code (VI, MC, AX, MA,) |
| | CardNumber | Integer | 0..1 | Credit card number |
| | SeriesCode | Integer | 0..1 | Security code |
| | ExpireDate | Date | 0..1 | Expiration date of the credit card. Mandatory date format: YYYY-MM-DD |
| | CVV | String | 0..1 | If is configured by FastPayHotels, return card CVV |
| | CardHolderName | String | 0..1 | Holder of the credit card |
| Address | | | | |
| StreetName | | String | 0..1 | Street name |
| StreetNmbr | | String | 0..1 | Street number |
| CityName | | String | 0..1 | City name |
| PostalCode | | String | 0..1 | Postal code |
| CountryName | Code | String | 0..1 | ISO 3 digit Country code |
| Contact | | | | |
| Telephone | | String | 0..1 | Customer's telephone number |
| Email | | String | 0..1 | Customer's e-mail address |
| ReservationIDs | | | 1 | |
| ReservationIDs | Value | String | 1 | Channel's booking reference |
| AdditionalInfoList | | | 0..1 | |
| AdditionalInfo | Code | String | 0..1 | If the channel wants to provide any additional relevant information (i.e. flight number, agent code...) can be supplied in this element |

4. Definition of Child Rate Calculation

The term First/Second/Third/... always apply to the children under same age range

The term A/B/C, applies to the different age range set up for the property

FirstChild A = First child under the age range A

SecondChildA = Second child under the age range A

FirstChildB = First child under the age range B

SecondChildB = Second child under the age range B

Example of calculation

Rates sent in ARI

```

<Rates>
  <Rate MinStayBasedRate="1">
    <MealPlans>
      <MealPlan Code="BB">
        <Price PaxType="Adult" PaxPrice="100.00"/>
        <Price PaxType="SingleUse" PaxPrice="90.00"/>
        <Price PaxType="ThirdAdult" PaxPrice="50.00"/>
        <Price PaxType="FirstChildA" PaxPrice="5.00"/>
        <Price PaxType="FirstChildB" PaxPrice="7.00"/>
        <Price PaxType="FirstChildC" PaxPrice="9.00"/>
        <Price PaxType="SecondChildA" PaxPrice="6.00"/>
        <Price PaxType="SecondChildB" PaxPrice="8.00"/>
        <Price PaxType="SecondChildC" PaxPrice="10.00"/>
      </MealPlan>
    </MealPlans>
  </Rate>
</Rates>

```

Property age range set up

Infant: 0 to 2 years old (Not included in Rate as are considered free)

Children: 3 to 12 years old (= Age Range A)

Teenager: 13 to 17 years old (= Age Range B)

Adult: from 18 years old

| | |
|-------------------------|---|
| Booking Request | 2ad + 1ch (5 yo) + 1ch (7 yo) |
| Rates parameter applied | (Adult PaxPrice x 2) + FirstChildA PaxPrice + SecondChildA PaxPrice |
| Final calculation | 200 + 5 + 6 = 211 |

| | |
|-------------------------|--|
| Booking Request | 2ad + 1ch (5yo) + 1ch (15 yo) |
| Rates parameter applied | (Adult PaxPrice x 2) + FirstChildA PaxPrice + FirstChildB PaxPrice |
| Final calculation | 200 + 5 + 7 = 212 |

| | |
|-------------------------|--|
| Booking Request | 2ad + 1ch (5yo) + 1ch (7 yo) + 1ch (15) |
| Rates parameter applied | (Adult PaxPrice x 2) + FirstChildA PaxPrice + SecondChildA PaxPrice + FirstChildB PaxPrice |
| Final calculation | 200 + 5 + 6 + 7 = 218 |

Ad = Adult

Ch = Child

Yo = Years Old

5. Notes

This documentation is a result of comprehensive analysis and is based on experience handling interfaces and automated, electronic message processing in B2B processes. Notwithstanding, the documentation is open to review and appraisal and might be modified and amended when and where it is deemed necessary by the relevant business units.

Once the implementation process is ready the provider has to contact FastPayHotels in order to arrange the certification testing.

FastPayHotels reserves the right to schedule this validation process for any convenient date within the next 15 days after receiving the request.